



**GMI's Perforated Disc Gaskets, Standard Clamp Style, are available Bonded or Removable and are manufactured to the highest quality standards in and for the processing industry from NBRs (Buna-N/Nitrile), EPDMs, VMQs (Silicone) and FKM's (Viton®) that are certified to FDA, USDA, 3-A Sanitary, USP Class VI and ANSI/NSF standards.**  
 Viton® is a registered trademark of E. I. DuPont De Nemours Company and DuPont Performance Elastomers.

**Perforated Metal Disc Data, Stainless Steel**

Hole Diameter*		Micron Equivalent	Holes Per Square		Centers			Open Area Percent %	Notes:
Inches	MM		Inch	MM	Inches	MM	Type		
0.0200	0.5080	508	952.0	1.476	0.0300	0.762	Straight	35	
0.0330	0.8380	838	331.0	0.513	0.0550	1.397	Straight	28	1
0.0450	1.1430	1143	230.0	0.357	0.0660	1.676	Straight	37	Info Only
0.0625	1.5880	1588	74.0	0.115	0.1250	3.175	Staggered	23	
0.0650	1.6510	1651	100.0	0.155	0.1000	2.540	Straight	33	Info Only
0.0938	2.3813	2381	47.0	0.073	0.1563	3.969	Staggered	33	
0.1000	2.5400	2540	47.0	0.073	0.1563	3.969	Staggered	37	
0.1030	2.6160	2616	57.0	0.088	0.1320	3.353	Straight	48	Info Only
0.1250	3.1750	3175	33.0	0.051	0.1875	4.763	Staggered	40	
0.2500	6.3500	6350	11.8	0.018	0.3125	7.938	Staggered	58	

Note 1. GMI's Standard Clamp Style.  
 \*Other hole diameters are available.

**GMI GASKETS® are Laser engraved with their respective Industry Part Number, GMI® Batch Number and Cure Date**

**Cross Reference Data**

MATERIAL → Style/Size/Color*	NBR Sulfur Cured	EPDM Peroxide Cured	VMQ (Silicone) Peroxide Cured	VMQ (Silicone) Platinum Cured	FKM (Viton*) Bisphenol Cured
Bonded, 1 to 6"	40MP-UP	40MP-EP	40MP-XP	40MP-XP-RX	40MP-SFYP
Removable, 1-1/2 to 6"	40MP-UP-R	40MP-EP-R	40MP-XP-R	40MP-XP-RXR	40MP-SFYP-R

\* Standard color is Black. Other colors available on request.

